

SAM 022826**UNIMAG Type PFA-60**

Group Lubrification device
Manufacturer UNIMAG
Type PFA-60
Etat new




Total Capacity 140 l
 Capacity 60 l/min
 Paper filter width 500 mm
 Paper filter length 90 m
 Pump motor installed power 25 W
 Dimensions:
 Length 1350 mm
 Width 720 mm
 Height 660 mm



APPLICATION:	
1. Surface Grinding Machine	5. Small Grinding Machine
2. Centerless Grinding Machine	6. Gear Grinding Machine
3. Internal/External Grinding Machine	7. Polisher
4. Honing machine	

DIMENSION DIAGRAM



PFA PAPER FILTER

FEATURES:

1. Applicable to both ferrous and non-ferrous particles.
2. Filter paper moves forward automatically when contaminants accumulate and clog it.
3. Filtration effect depends on paper accuracy. Choose from 50µ, 10µ and 15µ.
4. Not suitable for heavy machining for the sake of paper consumption. Use magnetic separator as pre-filter to reduce paper consumption.

Remark:

1. Standard accessory: one paper roll.
2. Special specification is available.



SPECIFICATION

MODEL	CAPACITY L/MIN	TANK VOL. L	L	A	B	C	H	PUMP (HP)	FILTER PAPER	WHEEL
PFA-30	30	120	1050	850	600	400	720	600	1/8 PP1/2"	25W
PFA-40	40	120	1300	1000	600	400	720	600	1/8 PP1/2"	25W
PFA-60	60	140	1350	1150	600	400	720	600	1/8 PP1/2"	25W
PFA-80	80	160	1500	1300	600	400	720	600	1/4 PP3/4"	25W
PFA-120	120	210	1500	1300	600	400	720	1/2 PP3/4"	40W	W1000MM
PFA-160	160	260	1600	1600	600	400	720	1/2 PP3/4"	40W	W1000MM
PFA-240	240	440	1550	1350	1000	450	1350	1 PP1"	60W	W1000MM
PFA-300	300	640	2150	1950	1000	450	1350	1 PP1"	90W	W1000MM
PFA-500	500	960	3240	2500	1000	450	1350	1.5 PP1.5"	150W	WHEEL